

A Ferragone Company

FERROLUX

METALS CO.

CAPABILITIES

Materials	Exposed and Unexposed Cold Rolled, Hot-Dipped and Electro Galvanized, Advanced High Strength Steels, Stainless, Aluminum
Thickness	.015" - .156"
Width	In: 24" - 80" Out: 4" - 78"
Width Tolerance	+/- .005
Number of Cuts	24 cuts maximum
Weight	24" or 20" ID: 70,000 lbs max
ID	20" and 24" incoming and outgoing
OD	30" - 84"
Inspection	Top and bottom surface, Unilux strobes, defect mapping, flagging
Tension Control	DC motors integrated throughout (uncoiler, arbors, synchro-wind, tension stand)
Overwind	Uncoiler and recoiler
Underwind	Uncoiler only (to reverse coil prime surface) if needed
Recoiling Accuracy	1/8" maximum oscillation
Gauge Measurement	Full profile x-ray charting
Oiling/Prelubing	Yes, multi-zone roll applicator or electrostatic
Crop Shear	Entry and exit
Packaging	As required
Quality System	IATF 16949:2016
Storage Capacity	500,000 sq. ft.
Atmosphere	Humidity and temperature controlled

IATF 16949:2016 registered



Ferrolux Metals Co. • 27800 W. Jefferson Ave. • Gibraltar, MI 48173

TOLL FREE: 877.566.6161 PHONE: 734.727.6161 FAX: 734.722.3251 EMAIL: info@ferrolux.com WEB: www.ferrolux.com